PTP – II

2" PORTABLE THERMAL PRINTER SERIES

- Outdoor usage
- Ultra light and compact design
- 7.4V,2000 mAh rechargeable li-battery
- RS232,Bluetooth, Raw-IR, USB interface
- Support android, ios, windows
- Sleep mode,Save power mode
- Anti-throw capacity can reach:1.5m with case protective
- Direct USB Charging

MODEL		PTP-II
Print	Printing method	Thermal line printing
	Printing speed	90mm/s(max)
	Resolution	203 dpi (8dots/mm)
	Effective printing width	48mm
Character	Character Set	ASCII,GB2312-80(Chinese)
	Print Font	ANK:8×16,9×17,9×24,12×24,16×18 GBK:24×24
	Flash	2M byte
	MCU	Flash:128KB SRAM:32KB
Paper spec.	Paper Type	Thermal paper
	Paper Diameter	40mm(Max.)
	Paper Thickness	55-90μm
	Paper Width	57.5±0.5mm
Paper supply method		Drop-in easy loading
Reliability	TPH	50km(12.5% print ratio)
Barcode	1D	EAN-13,EAN-8,CODE39,CODE93, CODE128,CODEBAR,ITF,UPC A,UPC-E
	2D	QR CODE
Text and graphic support		Figure,symbol,graph,curve, icon,multi-languages
Command		Compatible with ESC/POS command set
Sensor		No paper detection function
Interface	Wire	RS232,Mini USB
	Wireless	RAW-IR/Bluetooth2.0 or 4.0/Dual BT(2.0+4.0)
Power		2000mAh 7.4V/1600mAh,7.4V rechargeable Lithium battery
Recharge adapter		12V,0.8A/5V,2A adapter
Continous working time		8H
Physical	Weight	222g (Including battery)
	Dimension(WxLxH)	79x112x45mm
	Color	Black/Dark grey/White
Accessories	Standard accessories	Li-ion battery,AC adapter, USB cable, paper roll,user manual
	Optional accessories	Serial cable/CD/Car charger/Protective Case