CSN-A2/A2L 2" MICRO PANEL PRINTER SERIES

- Smart appearance
- Easy paper loading
- Low noise thermal printing
- Different interfaces optional
- Front panel make paper replacement easily
- Easily embedded to any kinds of instruments and meters

| MODEL | | CSN-A2/C |
|------------------------|-----------------------------|------------|
| Print | Printing Method | Thermal L |
| | Printing Speed | 90mm/s(r |
| | Resolution | 203dpi(80 |
| | Effective Printing Width | 48mm |
| Character | Character Set | ASCII,GB2 |
| | Print Font | ANK:9×1 |
| Paper spec. | Paper Type | Thermal F |
| | Paper Width | 57.5±0.5 |
| | Paper Thickness | 55-90μm |
| | Paper Roll Diameter | Max:38mi |
| Reliability | ТРН | 50km(12. |
| Interface | | RS232/TT |
| Power Supply (Adapter) | | DC5V-9V/ |
| Physical | Outline Dimension (WxLxH) | 111×65> |
| | Installation Port Size(WxL) | 103.3×57 |
| | Insert Depth | 50mm |
| | Color | Black/Beig |
| Environment | Operating Temp | 0°C~50° |
| | Operating Humidity | 10%~80% |
| | Storage Temp | -20° C~6 |
| | Storage Humidity | 10%~90% |

CSN-A2L Line (max) dots/mm) 2312-80(Chinese) 17,12×24,GBK:24×24 Paper 5mm n ۱m .5% print ratio) L/USB/Parallel //12V ×56.5mm 7.3mm ige/Orange С % 60°C %













Π