

	1	2	3	4	5	6	7	8	9	10	11								
A	<p>技术参数 (SPECIFICATION):</p> <p>温度范围 (TEMPERATURE RANGE): -40 ~ +70 °C</p> <p>额定电压 (VOLTAGE RATING): 125V</p> <p>额定电流 (CURRENT RATING): 1.5A</p> <p>接触电阻 (CONTACT RESISTANCE): ≤30mΩ</p> <p>绝缘电阻 (INSULATION RESISTANCE): ≥500MΩ</p> <p>耐压 (DIELECTRIC STRENGTH): 1000V AC / (50HZ) / MIN</p> <p>插拔力 (MATING AND UNMATING FORCE): 3 ~ 20N</p> <p>寿命 (DURABILITY): 750 CYCLES MIN</p>																		
B	<p>材料 (MATERIAL):</p> <p>塑座 (HOUSING): GLASS FILLED POLYESTER (UL 94V-0)</p> <p>插针 (CONTACT): PHOSPHOR BRONZE ϕ0.46mm</p> <p>镀层 (PLATING): GOLD PLATING OVER NICKEL</p> <p>外壳 (SHIELD): COPPER ALLOY PLATED NICKEL</p>																		
C	<p>PCB LAYOUT (TOP VIEW)</p> <p>RECOMMENDED</p>																		
D																			
E																			
F	<p>PCB LAYOUT (TOP VIEW)</p> <p>RECOMMENDED</p>																		
G	<p>一般公差</p> <table border="1"> <tr> <td>>30~</td> <td>±0.45</td> </tr> <tr> <td>>10~30</td> <td>±0.35</td> </tr> <tr> <td>~10</td> <td>±0.25</td> </tr> <tr> <td>角度:</td> <td>±5°</td> </tr> </table> <p>品名: RJ45 180度 全包无灯</p> <p>料号:</p> <p>型号: RJ45</p> <p>图号:</p> <p>版本:</p> <p>单位: mm</p> <p>比例: 1:1</p> <p>纸张: A4</p>											>30~	±0.45	>10~30	±0.35	~10	±0.25	角度:	±5°
>30~	±0.45																		
>10~30	±0.35																		
~10	±0.25																		
角度:	±5°																		
	<p>深圳市华联威电子科技有限公司</p> <p>HUA LIAN WEI TECHNOLOGY ELECTRONICS CO., LTD.</p>																		
	<p>绘图: _____ 日期: _____</p> <p>审核: _____ 日期: _____</p> <p>核准: _____ 日期: _____</p>																		
	<p>变更单号: _____ 绘制: _____ 日期: _____</p>																		
	<p>版次: _____</p>																		